



### SPECIFICATION

Recessed Paper Towel Dispenser shall hold and dispense 800 standard multi-fold or 600 standard C-fold paper towels. Cabinet and door shall be fabricated of 18-8 stainless steel, grade 304. Cabinet shall be 20 gauge with a 25mm wide return to lay flat against wall. All exposed surfaces shall have No. 4 satin finish. Full face door shall be 16 gauge free of mitres, welding or open seams with 24mm square horizontal returns to wall and 19mm rounded vertical edges. All four corners are welded and ground smooth with no open mitres. Door shall be attached to the edge of unit with a full length 5mm diameter stainless steel multi-staked piano hinge and shall be held closed with a flush rimless tumbler lock keyed alike to other JD MacDonald washroom equipment. Towel dispensing opening shall have a fully deburred edge for snag free dispensing and user safety. Structural assembly of body and door components shall be of welded construction.


### INSTALLATION

Unit is recessed mounted in wall using four (4) No. 10 self tapping screws (supplied by others) through concealed mounting holes provided. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use. Note that top of rough wall opening is 19mm below top of unit. Rough Wall Opening (RWO) required is 325mm x 675mm x 110mm.

### OPERATION

Towels are self-feeding until supply is depleted. Unit may be refilled with a partial load in-place and will continue to feed properly.

**Recessed Paper Towel Dispenser** shall be Model No. 9452 as supplied by JD MacDonald.

 All JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

