



SPECIFICATION

Recessed Paper Towel Dispenser and Waste Bin shall hold and dispense 800 standard multi-fold or 600 standard C-fold paper towels and shall have a waste capacity of 50.4 litres. Cabinet, waste bin and door shall be fabricated of 18-8 stainless steel, grade 304. Full face door shall be 16 gauge and shall be free of miters, visible welding or open seams with 24mm square horizontal returns to wall and shall have 19mm rounded vertical edges. All four corners are welded and ground smooth with no open miters. Door shall be attached to cabinet frame with a full length 5mm diameter heavy duty stainless steel multi-staked piano hinge and shall be held closed with a flush rimless tumbler lock keyed alike to other JD MacDonald washroom equipment. Towel dispensing slot shall have a fully deburred edge for snag-free dispensing and user safety. Waste bin shall be 16 gauge with hemmed edges and shall have 19mm rounded vertical edges to match door above and shall be fastened to cabinet with tamper resistant screws. Cabinet shall be 20 gauge with one-piece face trim construction 25mm wide with no miters or exposed welding and 6mm square returns to wall. Structural assembly of body and door components shall be of welded construction. All exposed surfaces shall have a No. 4 satin finish.

INSTALLATION

Unit is mounted in wall recess using four (4) No.10 self tapping screws (supplied by others) through concealed mounting holes provided. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use. Note that top of rough wall opening is 19mm below top of unit. Rough Wall Opening (RWO) required is 400mm x 1384mm x 102mm.

OPERATION

Towels are self feeding as extracted by user until supply is depleted. Waste bin is emptied manually on cycle determined by maintenance needs. A commercially available disposal trash bag is provided by owner, drape over edges of bin and locked into cabinet with bin.

Recessed Paper Towel Dispenser & Waste Bin shall be Model No. 9469 as supplied by JD MacDonald.



All JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

