



**Shown: Recessed Model No. 64676**  
Surface Mounted unit includes a trim

### SPECIFICATION

Surface Mounted Paper Towel Dispenser and Waste bin shall hold and dispense 800 standard multi-fold or 600 standard C-fold or 1100 standard single-fold paper towels and shall have a waste capacity of 26.5 litres. Towel dispenser, door, frame, waste bin and cabinet shall be fabricated of alloy 18-8 gauge stainless steel, grade 304. Cabinet shall be 20 gauge with a 25mm wide perimeter return to lay flat against wall. Full face door shall be 18 gauge with a 13mm square return to wall with no visible open seams on door face. Door shall be attached to the cabinet at side with a full length 5mm diameter stainless steel multi-staked piano hinge and shall be held closed with tumbler locks keyed alike to other JD MacDonald washroom equipment. Towel dispensing slot shall have a fully hemmed-in rolled edge for snag-free dispensing and user safety. Waste bin shall have hemmed edges for safety. Structural assembly of all components shall be of welded construction. Waste bin door shall be attached to cabinet with a spring-loaded stainless steel piano hinge and shall have the international waste symbol on face.


### INSTALLATION

Unit is surface mounted on wall with No. 10 self tapping screws (supplied by others) through concealed mounting holes provided. Surface mounting collar is installed on cabinet prior to mounting on wall following procedure described on Surface Mounting Collar data sheet. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

### OPERATION

Towels are self feeding until supply is depleted. Unit may be reloaded with a partial load in place and will continue to feed properly. Waste bin is emptied manually on cycle determined by maintenance needs. Adapter permits changing from C-fold to multi-fold towel dispensing.

**Surface Mounted Paper Towel Dispenser & Waste Bin** shall be Model No. 64676-9 as supplied by JD MacDonald.

 All JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

