



### SPECIFICATION

Double Toilet Roll Holder shall hold and dispense two (2) standard or two (2) 133mm diameter 1800 sheets tissue rolls and shall have door, door frame, and dispensing mechanism fabricated of alloy 18-8 stainless steel, grade 304, 18 gauge; cabinet body shall be same grade, 22 gauge. All exposed surfaces shall be No. 4 satin finish and be protected during shipment with a PVC film easily removable after installation. Internal mechanism levers shall be fabricated of molded high-impact resistant plastic for smooth operation. Structural assembly of body and door components shall be of welded construction. Door hinge shall be of heavy-duty stainless steel 5mm diameter rivets. Door shall have 19mm rounded vertical edges with all corners welded and ground smooth with no open miters shall be held closed with a flush rimless tumbler lock keyed alike to other JD MacDonald washroom equipment. Vandal resistant rollers shall be of molded high-impact resistant plastic with integral molded-in stainless steel end pins and two (2) rollers shall be supplied.

### INSTALLATION

Unit is surface mounted on wall or partition using four (4) No. 10 self tapping screws (supplied by others). Top two mounting holes through back are "keyhole" slots for ease in hanging unit on pre-installed screws. Bottom two mounting holes are horizontal slots for ease of adjustment. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

### OPERATION

Reloading instructions are printed on graphic label inside door. Bottom roll is depleted prior to top roll automatically dropping into lower position for use. Empty rollers can not be removed without key unlocking door.

**Double Toilet Roll Holder** shall be Model No. 9030 as supplied by JD MacDonald.

