



### SPECIFICATION

Bench Mounted Soap Dispenser shall hold and dispense 1 litre of liquid soap, lotion or detergent. Dispenser stem and 102mm spout shall be fabricated of stainless steel with rubber "duck bill" check valves and an O-ring seal. Valve body, internal parts, basin nut, threaded shank and globe adapter shall be fabricated of molded plastic. Spring, escutcheon washer, stem retainer collar and screw shall be fabricated of stainless steel. Escutcheon plate shall be fabricated of chrome plated brass. Soap container shall be fabricated of vandal-resistant polyethylene plastic. Valve and spout shall rotate after unit is installed.

### INSTALLATION

Unit is typically located adjacent to a flush mounted bench, through 22mm diameter cut out (by others) in counter top. An adjustable threaded shank allows for installation in counter tops up to 89mm thick.

### OPERATION

Soap is manually dispensed by pushing down on the spout stem. Dispenser is refilled by using the special refill key to unlock the escutcheon and remove the valve body with dip tube from the shank to expose reservoir opening. Dispenser is refilled on a cycle determined by maintenance needs.

**OPTIONS** Spout option may be combined with globe option. Specify option by adding suffix to Model No (e.g. 0332-CD).

Model	Capacity	Spout Length
0332	1.0 litres	102mm
0332-C	0.6 litres	102mm
0332-CD	0.6 litres	152mm
0332-D	1.0 litres	152mm

**Bench Mounted Soap Dispenser** shall be Model No. 0332 as supplied by JD MacDonald.

