



## SPECIFICATION

Surface Mounted Liquid & Antiseptic Soap Dispenser shall hold and dispense up to 1.18 litres of a wide variety of antiseptic and liquid soaps, shampoos, lotions or detergents. Unit shall not dispense liquid material containing abrasives such as pumice. Dispenser shall be fabricated of transparent smoked grey tank and opaque grey base, push bar and cover. Valve shall be constructed of concealed plastic body with stainless steel and plastic internal parts. Valve operation shall require no more than 2.26kg pressure to actuate and require no grasping or twisting by operator. Unit cover shall be sloped and shall overlap edges to prevent top use as a shelf and to keep water spray out. Cover shall be retained by a concealed locking release.


## INSTALLATION

Unit is surface mounted to wall or partition by means of a bracket (bracket & hardware provided). Unit is secured to concealed bracket and locked in place by concealed snap latch. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

## OPERATION

Soap is manually dispensed by depressing push bar. Unit is refilled through tamper resistant top cover. Soap tank will continue to feed properly until empty. Tank supply is refilled manually on cycle determined by maintenance needs. Clear tank provides continuous view of soap level.

**Surface Mounted Liquid & Antiseptic Soap Dispenser** shall be Model No. 0340 as supplied by JD MacDonald.

 All JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

