



### SPECIFICATION

Surface Mounted Horizontal Soap Dispenser shall hold and dispense up to 1.18 litres of liquid soap, lotion or detergent. Dispenser shall be fabricated of alloy 18-8 stainless steel, grade 304, 20 gauge. All exposed surfaces shall be No. 4 satin finish. Valve shall be constructed of a plastic valve body and push button with stainless steel and plastic internal parts. A liquid level indicator shall be provided above valve. Unit shall have a hinged stainless steel refill door on top of unit which is opened with special key (supplied) to open. Soap tank will continue to feed properly until empty. Tank supply is refilled manually on cycle determined by maintenance needs.


### INSTALLATION

Unit is surface mounted to wall or partition by means of a bracket (bracket & hardware provided). Unit is secured to interlocking wedge bracket and locked in place by means of a locking screw installed through hinged refill door. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

### OPERATION

Soap is manually dispensed by depressing push button. Unit is refilled through hinged refill door at top requiring special key (supplied) to open. Soap tank will continue to feed properly until empty. Tank supply is refilled manually on cycle determined by maintenance needs.

**Surface Mounted Horizontal Soap Dispenser** shall be Model No. 0345 as supplied by JD MacDonald.

 All JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

