



SPECIFICATION

Surface Mounted Soap Dispenser shall dispense 0.40 litres of soap, lotion or detergent. Housing and filler cap shall be fabricated of alloy 18-8 stainless steel, grade 304. Housing shall have four (4) top to bottom viewing slots and shall hold a removable plastic globe. Filler cap shall be permanently chained to housing. Valve shall be constructed of a chrome-plated brass body with stainless steel and plastic internal parts. All exposed metal surfaces shall be mirror finish.


INSTALLATION

Unit is secured to a concealed (tamper resistant) wall plate which is surface mounted to wall or partition using No. 10 self tapping screws (supplied by others). For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

OPERATION

A liquid thin viscosity soap is manually dispensed by depressing push button. Unit is refilled by unlocking filler cap using a service key. Soap will continue to feed properly until empty. Tank supply is refilled manually on cycle determined by maintenance needs. In most cases a funnel may have to be used to avoid soap build up on the threaded cap lock.

Surface Mounted Soap Dispenser shall be Model No. 0351 as supplied by JD MacDonald. Model No. 0352 (not shown) similar to Model No. 0351, but dispenses lather.

 All JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

