



### SPECIFICATION

Surface Mounted Disposable Cartridge Soap Dispenser unit shall be fabricated of alloy 18-8 stainless steel, grade 304. Dispenser housing and wall bracket shall be 16 gauge. Dispenser door shall be 22 gauge, attached to unit at the bottom with a full length 5mm diameter stainless steel multi-staked piano hinge and held closed with a tumbler lock keyed alike to other JD MacDonald washroom equipment. Dispenser lever shall be a ruggedized Zamak alloy casting. All exposed surfaces shall have No. 4 satin finish and be protected during shipment with PVC film that shall be easily removable after installation. Valve shall be fabricated of heavy duty vinyl and shall be attached to a disposable soap cartridge.


### INSTALLATION

Unit is surface mounted to wall or partition using No. 10 screws (supplied by others) through concealed mounting holes. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

### OPERATION

Soap is forced through disposable valve by pulling a lever forward. Disposable cartridges are available to dispense soap, hand lotion, heavy duty cleaner, waterless cleaner and antiseptic soap and are typically good for 1500 washings.

**Surface Mounted Disposable Cartridge Soap Dispenser** shall be Model No. 5001-SS as supplied by JD MacDonald.

 All JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

