



SPECIFICATION

Recessed Soap Dispenser shall hold and dispense 1.7 litres of liquid and lotion soaps, synthetic detergents and antibacterial soaps containing PCMX and/or Triclosan. Dispenser tank, door, mounting frame and push button valve shall be fabricated of alloy 18-8 stainless steel, grade 304. Cabinet shall be fabricated of 20 gauge with a 25mm wide perimeter return to lay flat against wall. Door and tank shall be fabricated as one integral unit from 18 gauge. Door shall have a 13mm square return to wall with no visible open seams on door face and shall be held closed with a tumbler lock keyed alike to other JD MacDonald washroom equipment. A tamper resistant sight gauge shall be provided. Valve shall be constructed of a chrome-plated brass body with stainless steel and plastic internal parts. Valve operation shall have no more than 2.26kg of pressure to actuate without grasping or twisting by operator. All exposed surfaces shall be No. 4 satin finish and be protected during shipment with a PVC film easily removable after installation.


INSTALLATION

Unit is mounted in wall recess using two (2) No. 10 self tapping screws (supplied by others) through concealed mounting holes provided. Note that top of rough wall opening is 14mm below top of unit. Rough Wall Opening (RWO) required is 230mm x 125mm x 110mm. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

OPERATION

Soap is manually dispensed by pushing valve button until supply is depleted. Unit may be reloaded easily by removing door/tank assembly with a partial load in place and will continue to feed properly. Tank supply is replenished manually on cycle determined by maintenance needs.

Recessed Soap Dispenser shall be Model No. 6326 as supplied by JD MacDonald.

 All JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

