



SPECIFICATION

Surface mounted Automatic Stainless Steel Touch Free Soap Dispenser shall hold and dispense up to 1000ml of liquid and lotion soaps, synthetic detergents and antibacterial soaps containing PCMX and/or Triclosan with a viscosity range of between 1 and 3500 mPa.s or cP (MilliPascal-sec or Centipoise). Dispenser body shall be fabricated of alloy 18-8 stainless steel, type 304 and black ABS. All exposed stainless steel surfaces shall be No. 4 satin finish. Dispenser shall be powered by six (6) AA-size (1.5V) batteries (not supplied) and shall operate automatically from IR sensor that shall activate soap dispensing when hands are placed in sensor zone. Sensor detection range shall be self adjusting. Dispenser shall pump for 1 to 5 seconds during each activation as preset by owner. A tamper resistant soap level viewing window shall be provided. Unit shall have a removable access lid on top of unit which is opened with a special key provided.

INSTALLATION

Unit is surface mounted to wall or partition by means two (2) No. 8 screws. Unit is secured by means of a third screw concealed inside locking removable lid. Remove soap dispenser casing, use key to unlock. Remove soap container. Hang soap dispenser and insert screws into dowels and tighten. A mounting template is provided. Overall size: 104mm x 235mm x 124mm.

OPERATION

Soap is automatically dispensed when hands are placed in sensor zone. Pumping duration is entered by owner at setup. Unit is reloaded by unlocking and removing lid at top with special key (supplied) and removing and refilling internal soap container. Soap dispenser will continue to feed properly until empty. Tank supply is replenished manually on cycle determined by maintenance needs. A complete instruction sheet is provided with each unit.

Automatic Stainless Steel Touch Free Soap Dispenser shall be Model No. 0360 as supplied by JD MacDonald.

